

VERS

QUICK REFERENCE



QTLighting

VERS

VERSATILE LINEAR FIXTURES



Lumens/ft:
Up to 1024
at 9.0W/ft



Color
Temperature:
1900K-5500K



CRI:
Up to 99



Color:
SW, SW-HE, DW-HE,
SC, RGB, RGBW,
RGBW-HE



Options comply with
Buy American Act



All VERS fixtures have
Declare labels and are
Red List Approved

	PROFILE		PROFILE
<p>VERS-PROUD (01)</p> <p>Utilizes an extruded lens that sits proud of the fixture for maximum variations of LED sources</p>	<p>.88"W X .64"H</p> <p>99°-115°</p> <p>DF, FR, PR</p>	<p>VERS-ENCAPSULATED (06)</p> <p>Wet-rated VERSatile fixture encapsulated in polyurethane, providing protection from moisture, dust and dirt</p>	<p>.88"W X .60"H</p> <p>120°</p> <p>CL, TL</p>
<p>VERS-FLUSH (02)</p> <p>Features a co-extruded lens with an internal reflector, maximizing efficiency for improved lumen output</p>	<p>.88"W X .60"H</p> <p>102°-115°</p> <p>DF, PR</p>	<p>VERS-LOUVER (07)</p> <p>A VERSatile fixture with an internal louver that is designed to eliminate glare</p>	<p>.88"W X .60"H</p> <p>85°-95°</p> <p>DF, CL</p>
<p>VERS-CLEAR (03)</p> <p>The high quality clear lens allows for maximum variations of LED sources and the most delivered lumens of the VERS Family</p>	<p>.88"W X .64"H</p> <p>100°</p> <p>CL</p>	<p>VERS-INSERT (08)</p> <p>A VERSatile fixture that offers prismatic or batwing insert options</p>	<p>.88"W X .64"H</p> <p>100°-115°</p> <p>BAT, GC</p>
<p>VERS-GRAZER (04)</p> <p>Optically enhanced VERSatile fixture with grazing properties ranging from 12° to 36°</p>	<p>.88"W X .84"H</p> <p>12°-36°</p> <p>OPTIC</p>	<p>VERS-ASYMMETRIC (09)</p> <p>Features an extruded asymmetric lens with a proprietary diffusing agent that allows for light to be focused in a tight 45° beam that is shifted 30° off center</p>	<p>.88"W X .63"H</p> <p>45° SHIFTED 30° OFF CENTER</p> <p>OPTIC</p>
<p>VERS-OPTICS (05)</p> <p>Optically enhanced VERSatile fixture provides precision beam control for when precision lighting is needed</p>	<p>.88"W X .66"H</p> <p>40°-50°</p> <p>OPTIC</p>	<p>VERS-DROP (10)</p> <p>Utilizes an extruded drop lens that sits proud of the fixture for maximum variations of LED sources and three sided diffused illumination</p>	<p>.88"W X 1.20"H</p> <p>120°</p> <p>DF, PR</p>

Diagrams shown in actual size
▲ Beam angle

Diode Visibility

DeCoster Pool House
Lighting Designer: Patdo Light Studio
Location: Greenwich, CT
Products: VERS-OPTICS (05), QOM-eLED+0-10V,
PIVOT BRACKET

